

130-bbl Kill Trailer

Kill trucks haul various oilfield-related fluids to kill or control the flow of oil and gas wells. PCI Manufacturing's 130-bbl kill trailers are the latest offering in the company's product line. Standard features include three-point suspension, two-speed crank landing legs and ¼" ASTM A36, sub-arc'd steel barrel; each barrel is fully gusseted and padded to withstand the rigors of both on and off road.

No need to worry about stepping over hoses or through mud—PCI's kill trailer allows easy access from the ground to the upper walkway. The long wedge sump offers room for 4" and 6" loading lines, giving you all the flexibility you need to handle a variety of fluids.

These vacuum trailers are built according to PCI's strict standard, fully inspected and tested to ensure that every weld and brake light meets or exceeds DOT and OSHA standards.

We keep our word, so you can keep yours.



All PCI products are designed and built in-house, with a full quality-control team on hand to ensure the highest quality and consistency, providing customers a low-maintenance, long-term asset.

2901 North Freeway ♦ Fort Worth, Texas 76106

817-624-3181 ♦ 800-709-3184 ♦ FortWorthTruck.com



Standard Kill Trailer Specifications:

- ✓ 130-bbl capacity: 50 bbl front/80 bbl rear
- ✓ Barrels are sub-arc welded and tested to 20 psi design pressure
- ✓ ASTM A36 steel, ¼" heads and shell
- ✓ Ultra-heavy-duty rear bumper
- ✓ Adjustable kingpin plate
- ✓ Two-speed crank landing legs
- ✓ Full-length hose troughs with drains
- ✓ Platform with handrails and ladder covering both manways
- ✓ 2" front and rear compartment sight glasses; one on both sides of crow's nest
- ✓ DOT-approved LED lighting with custom fit, plug and go wiring harness
- ✓ Dual tool boxes with heavy duty lids and door chains mounted within a steel cradle
- ✓ 15.0 psi pressure/vacuum vents
- ✓ Three 20" top manways; one camlock manway for each compartment and one rear manway with wingnuts for cleanout
- ✓ Two unloading points at rear of tank with 4" butterfly valves
- ✓ 4" line from rear sump to front of trailer with three outlets: one to driver's side, one to passenger's side, and one out of bottom, forward stopping just behind landing leg area—all with butterfly valves
- ✓ Ridged pipe racks to hold 2" × 10' hard line
- ✓ Three-point, eight-leaf suspension
- ✓ 11R-24.5" chip-resistant radial tires
- ✓ 25,000-lb axle with auto slack adjusters
- ✓ Carboline Phenoline® 310 two-part epoxy coating
- ✓ Primer plus one-color Strathmore DTM paint

Options:

PCI Manufacturing offers the following options, allowing customers to create a custom tank, built to satisfy their specific needs.

- Optional pre-fabricated hose-trough mount for trailer-mounted pumps
- Spray-in liner for hose troughs
- 8" float ball
- Hoses cut to length
- Air-ride suspension
- Drip tray under butterfly valves

2901 North Freeway ♦ Fort Worth, Texas 76106

817-624-3181 ♦ 800-709-3184 ♦ WWW.FORTWORTHTRUCK.COM