



130-BBL VACUUM TRAILERS

PCI Manufacturing's vacuum trailer is the latest addition to the company's product line. Standard features include three-point suspension, two-speed crank landing legs and quarter-inch SA-36 steel barrel; each barrel is fully gusseted to withstand the rigors of both on and off road.

No need to worry about stepping over hoses or through mud—PCl's vacuum trailer allows easy access from the ground to the upper walkway. The wedge sump offers room for 4-inch and 6-inch loading lines, giving you all the flexibility you need to accomplish any job.

These vacuum trailers are built according to a rigorous standard, fully inspected and tested to ensure that every weld, brake light and coat of paint functions flawlessly.

We keep our word, so you can keep yours.



All PCI products are designed and built in our state-of-the-art facility, with complete in-house fabrication, blasting and painting departments. Absolute control of the manufacturing process ensures the highest quality and consistency.

Our equipment is built to provide you with a long-term investment while meeting OSHA safety standards. PCI Manufacturing's low-maintenance, mobile designs ensure that your investment can be used again and again.





Standard Vacuum Trailer Specifications:

- √ 130-bbl capacity
- √ 14.7-psi design pressure
- ✓ Two internal baffles made of flat plate and strapped to ensure full coating coverage
- ✓ External 2.5" strap supports
- ✓ SA-36 steel, ¼" heads and shell
- ✓ Rectangular tubing bumper
- ✓ Ultra-heavy-duty rear bumper with D pull ring
- ✓ Adjustable kingpin plate
- ✓ Two speed crank landing legs
- ✓ Four wide hose troughs with drains and bed liner coating.
- ✓ DOT-approved LED lighting with exclusive wiring harness
- ✓ Dual tool boxes: front hose trough and rear mounts
- √ 15.0 psig pressure/vacuum vents
- ✓ Three 20" top man ways
- √ 12" primary scrubber
- √ 10-gallon secondary scrubber
- ✓ Three-point, eight leaf suspension
- √ 11×24.5 radial tires
- ✓ Axle: round 22,500-lb with auto slack adjusters
- ✓ Carboline® 310 two-part epoxy coating
- ✓ Primer plus one-color Strathmore DTM paint
- ✓ Walkways/handrails: side and rear entry to catwalk
- ✓ 2" sight-glass fittings, front driver and rear passenger side
- ✓ Pre-fabricated hose-trough mount for trailer-mounted pumps

Options:

PCI Manufacturing offers the following options, allowing customers to create a custom tank, built to satisfy their specific needs.

- Gel/belly lines or belly nipples
- Hose trough mounted vacuum pumps (complete with catch muffler and ready-to-install pump)
- 2" sight glasses
- 8" float ball
- Hoses cut to length
- Pump/engine kits (self-contained)
- Air-ride and/or single-point suspension
- Drip tray under butterfly valves
- Water-transport only versions